



PCVISION

## Technical specifications

Product	PCV-DPHMH13-2K	PCV-DPHMH12-4K	PCV-DPHMH28-2K	PCV-DPHMH14_5S	PCV-DPHMH24-4K	PCV-DPHMH39-2K	PCV-DPHMH14-2K
Part number	PCV-DPHMH13-2K	PCV-DPHMH12-4K	PCV-DPHMH28-2K	PCV-DPHMH14-5S	PCV-DPHMH24-4K	PCV-DPHMH39-2K	PCV-DPHMH14-2K
Product type	Video Splitter Box	Video Splitter Box	Video Splitter Box	Video Splitter Box	Video Splitter Box	Video Splitter Box	Video Splitter Box
Form factor	PCBA+ Black Metal Box	PCBA+ Black Metal Box	PCBA+ Black Metal Box	PCBA+ Black Metal Box	PCBA+ Black Metal Box	PCBA+ Black Metal Box	PCBA+ Black Metal Box
Input connector (video & audio support)	DP 1.4 with Audio	DP 1.4 with Audio	DP 1.4 with Audio	DP1.2 / HDMI 1.4-no Audio	DP 1.4 with Audio	DP 1.4 with Audio	DP 1.4 with Audio
Max input resolutions	--5760x1200@120Hz 5760x3240@50Hz	7680x2160@60Hz 7680x4320@30Hz	7680x1200@100Hz x2 7680x4320@30Hz x2	7680x1080@60,1920x4320@60 5760x1080@60,1920x3240@60 3840x2160@60Hz	7680x2160@60Hz x2 7680x4320@30Hz x2	5760x1200@120Hzx3 5760x3240@50Hzx3	7680x1200@100Hz 7680x4320@30Hz
Output connectors (video & audio support)	HDMI2.0withAudio	HDMI2.0withAudio	HDMI2.0withAudio	HDMI 1.4 not Audio Support	HDMI 2.0withAudio	HDMI 2.0withAudio	HDMI 2.0withAudio
Max output resolutions	1920x1200@120Hzx3 1920x3240@50Hz x3	3840x2160@60Hzx2 3840x4320@30Hzx2	1920x1200@100Hzx8 1920x4320@30Hzx8	1920x1080@60Hzx3/x4	3840x2160@60Hzx4 3840x4320@30Hzx4	1920x1200@120Hzx9 1920x3240@50Hz x9	1920x1200@100Hzx4 1920x4320@30Hzx4
<b>Configurations</b>							
Out-of-box supported configurations	--	--	--	--	--	--	--
Rotation (Support by Visuade)	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support
Multi-unit support (Support by Visuade)	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support
Bezel management (Support by Visuade)	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support
Clone mode (Support by Visuade)	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support
HDCP support	Support	Support	Support	Support	Support	Support	Support
<b>Video &amp; audio processing</b>							
Video scaling (Support by Visuade)	-Pixel to Pixel without scaling-	Pixel to Pixel without scaling	Pixel to Pixel without scaling	Pixel to Pixel without scaling	Pixel to Pixel without scaling	Pixel to Pixel without scaling	Pixel to Pixel without scaling
Video cropping	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support	HW Not Support
Audio format	LPCM, AC-3, MP3, DTS 4 Channel	LPCM, AC-3, MP3, DTS 4 Channel	LPCM, AC-3, MP3, DTS 4 Channel	Not Support	LPCM, AC-3, MP3, DTS 4 Channel	LPCM, AC-3, MP3, DTS 4 Channel	LPCM, AC-3, MP3, DTS 4 Channel
Audio sampling rate	32KHz,44.1KHz,48KHz, Max 128KHz	32KHz,44.1KHz,48KHz, Max 128KHz	32KHz,44.1KHz,48KHz, Max 128KHz	Not Support	32KHz,44.1KHz,48KHz, Max 128KHz	32KHz,44.1KHz,48KHz, Max 128KHz	32KHz,44.1KHz,48KHz, Max 128KHz
<b>Control &amp; update protocols</b>							
Control interface	mUSB	mUSB	mUSB	mUSB	mUSB	mUSB	mUSB
IP version / IP addressing	--Not Support	Not Support	Not Support	Not Support	Not Support	Not Support	Not Support
Command & control protocols	--UART	UART	UART	UART	UART	UART	UART
Firmware update	--No Support	No Support	No Support	No Support	No Support	No Support	No Support
<b>Color space</b>							
Input color space	--8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)	8bpp	8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)
Output color space	--8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)	8bpp	8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)	8/10bpp (12/16bpp Option)
<b>Environmental &amp; power consumption</b>							
Operating conditions	0~50°C	0~50°C	0~50°C	0~50°C	0~50°C	0~50°C	0~50°C
Power supply	+5V	+5V	+5V	--12V	+5V	+5V	+5V
Maximum power consumption	--5W	--8W	--15W	--20W	--15W-	--15W-	--8W
<b>Hardware</b>							
Dimensions (WxHxD)/weight	175x38x105mm/600g	175x38x105mm/600g	175x38x105mm/600g	110x30x155mm/700g	175x38x105mm/600g	175x38x105mm/600g	175x38x105mm/600g
Regulatory / environmental compliance	--	--	--	--	--	--	--
Warranty	1years	1years	1years	1years	1years	1years	1years
<b>Accessories (Option not include)</b>							
	DC 5V 3A Adapter 110V/220V DP to DP 30cm Cable mDP to DP 30cm Cable USB Cable	DC 5V 3A Adapter 110V/220V DP to DP 30cm Cable mDP to DP 30cm Cable USB Cable	DC 5V 3A Adapter 110V/220V DP to DP 30cm Cable mDP to DP 30cm Cable USB Cable	DC 12V 3A Adapter 110V/220V DP to DP 30cm Cable mDP to DP 30cm Cable HDMI 30cm Cable USB Cable	DC 5V 3A Adapter 110V/220V DP to DP 30cm Cable mDP to DP 30cm Cable USB Cable	DC 5V 3A Adapter 110V/220V DP to DP 30cm Cable mDP to DP 30cm Cable USB Cable	DC 5V 3A Adapter 110V/220V DP to DP 30cm Cable mDP to DP 30cm Cable USB Cable