### **MAGEWELL**

# **Ultra Stream HDMI Technical Specifications**

Copyright (c) 2011–2022 Magewell Electronics Co., Ltd. All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

HDMI, the HDMI logo and High-Definition Multimedia interface are trademarks or registered trademarks of HDMI Licensing LLC.

Revised 02/06/2022

### **Input Features**

- Max HDMI input & loop-through signals:
  - 4096x2160 4:2:0 60fps
  - 4096x2160 4:4:4/4:2:2 30fps
- Custom EDID
- Supported HDMI inputs include:
  - 4096x2160p/3840x2160p 23.98/24/25/29.97/30/59.94/60
  - 2560x1080p 23.98/24/25/29.97/30/50/59.94/60
  - 1920x1080p 23.98/24/25/29.97/30/50/59.94/60/100/119.88/120
  - o 1920x1080i 25/29.97/30/50/59.94/60
  - 1280x720p 23.98/24/25/29.97/30/50/59.94/60/144
  - o 720x576p 50/100/144
  - o 720x576i 25/50
  - o 720x480p 59.94/60/144
  - o 720x480i 29.97/30
- 8/10/12-bit color
- Input & loopthrough 8-Channel, 24-bit HDMI embedded audio, 192kHz sample rate
- Input audio from 3.5mm microphone
- HDMI Input and loop-through interfaces: HDMI 1.4a, DVI-D

### **Encoding Features**

- · Dual stream encoding: main stream and sub stream
- Max bitrate:
  - Main Stream 8Mbps
  - o Sub Stream 2Mbps
- · Supported resolutions:
  - HD: 1920x1080, 1600x1200, 1600x900, 1440x1080, 1440x900, 1280x1024, 1280x960, 1280x800, 1280x720, 1024x768
  - SD: 960x540, 800x600, 768x576, 720x576, 720x540, 640x480, 640x360, 480x360, 480x270
- Supported frame rates: 60/59.94/50/30/29.97/25/24/15/10/5fps
- H.264/H.265(HEVC) video encoders
- Encoding 2-channel AAC at 48kHz, 16-bit
- Supported audio bitrates: 256/192/128/96/64/48/32/16 kbps
- Extracting audio from HDMI signal and output through 3.5mm headphone
- · Encoding videos after de-interlacing

## **Streaming Features**

- Natively support streaming to Facebook, Twitch and YouTube
- Supported streaming protocols including RTSP/RTMP/RTMPS
- Up to 2 streaming sessions simultaneously

## **Recording Features**

- · Recording to a USB flash drive, internal SD storage and paired mobile device simultaneously
- To a USB Flash Drive
  - o support auto-recording, normal recording
  - o recording as MP4 or MOV files
  - Recording duration can be 5/10/30/40/50/60/90/120 min
  - Downloading recorded videos via WebUI

- To internal SD storage (32GB)
  - o support auto-recording, loop-styled or normal recording
  - o recording as MP4 or MOV files
  - Recording duration can be 5/10/30/40/50/60/90/120 min
  - uploading recorded videos to a specified FTP server (FTP over TLS is supported), your Dropbox and Google Drive via WebUI
  - Downloading recorded videos via WebUI
- To paired mobile device
  - o recording as MP4 files
  - o taking still image snapshots during recording
  - o timer recording at 15s, 30s, 1min, 2min, 5min

### **Configuration Management**

- Register with 2 Magewell Cloud platforms
- · Remote control via Application, WebUI and Magewell Cloud
- Provide comprehensive information regarding the system information of device and working status in real-time
- Configure parameters of volume and color, input and output signals, stream profiles, no signal image, the Ethernet and Wi-Fi connection, as well as date and time
- Update firmware
- WebUI supports IE/Edge/Firefox/Chrome/Safari/Opera web browsers
- Provide HTTP APIs

#### **Network**

- Wired Ethernet network: 10/100/1000Mbps
- Wi-Fi 802.11 a/b/g/n/ac
- 3G/4G USB mobile broadband Modem (not included)
- Bluetooth 4.0 BLE

#### **LED Indicators**

- Indicate the state of the input signal, Ethernet Network, Wi-Fi, USB flash drive
- · Indicate the working state of the device: startup, recording, streaming, updating

# **Power Supply and Consumption**

- DC 5V/2A
- Max power consumption: ~9.6 W

#### **Form Factor**

94.20mm x 94.20mm x 22.30mm

#### **Accessories**

- AC adapter
- HDMI cable

## **Working Environment**

- Operating temperature: 0 to 40 deg C
- Storage temperature: -20 to 70 deg C
- Relative humidity: 5% to 90% non-condensing