

# MAGEWELL

## Ultra Encode SDI Plus Technical Specifications

Copyright (c) 2011–2023 [Magewell Electronics Co., Ltd.](http://www.magewell.com) All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

NDI is trademark or registered trademark of NewTek Inc.

Revised on 07/11/2023

### Input & Loop-through

- Video
  - Supports SD (ST 259)/HD (ST 292)/3Ga (ST 425)/3Gb (ST 425)/3Gb-DL(ST 425)/3Gb-DS (ST 425)/6G (ST 2081) standards
  - Typical resolution/frame rate:
    - 4096x2160p 23.98/24/25/29.97/30
    - 2560x1440p/2048x1080p/2048x1080i 23.98/24/25/29.97/30/47.95/48/50/59.94/60
    - 1920x1080p/1920x1080i 23.98/24/25/29.97/30/47.95/48/50/59.94/60
    - 1280x720p 25/29.97/30/50/59.94/60
    - 720x576 25p/50i (PAL SD)
    - 720x480 29.97p/59.94i (NTSC SD)
  - Color sampling: YCbCr 10-bit 4:2:2, YCbCr 10-bit 4:4:4, YCbCr 12-bit 4:2:2, YCbCr 12-bit 4:4:4
- Audio
  - SDI embedded audio: 16-Channel, 24-bit, 192kHz sample rate
  - Audio from 3.5 mm LINE IN: 2-Channel, 24-bit, 192kHz sample rate

### Encoding Features

- Video
  - Bitrate:
    - NDI<sup>®</sup> HX3: up to 62.0Mbps, down to 1.5Mbps
    - Others: up to 32.0Mbps, down to 256kpbs
  - Dual-stream encoding: main stream and sub stream
  - Main stream
    - Resolution/frame rate:
      - 4096x2160p/3840x2160p 30/29.97/25/24/23.976/15/10/5
      - 2560x1440p/2048x1080p/1920x1200p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1920x1080p/1920x720p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1664x936p/1600x1200p/1600x900p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1440x1080p/1440x900p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1280x1024p/1280x960p/1280x800p/1280x720p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1024x768p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1024x576p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 960x540p/800x600p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 768x576p/720x576p/720x540p/720x480p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 640x480p/640x360p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 480x360p/480x270p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
    - Native CEA–608/608 over 708 captions
  - Sub stream
    - Supports enabling/disabling sub stream
    - Resolution/frame rate:
      - 1920x1080p/1920x720p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1664x936p/1600x1200p/1600x900p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1440x1080p/1440x900p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1280x1024p/1280x960p/1280x800p/1280x720p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1024x768p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 1024x576p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 960x540p/800x600p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 768x576p/720x576p/720x540p/720x480p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 640x480p/640x360p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
      - 480x360p/480x270p 60/59.94/50/30/29.97/25/24/23.976/15/10/5
  - H.264/H.265 (HEVC) Codec:
    - System timecode or RP–188 standard timecode for SEI Message setting

- H.265 (HEVC) SEI message supports carrying interlacing signal mark
  - Video aspect ratio conversion
  - Image rotation: 0°, 90°, 180°, 270°
  - Cropping
  - Output 3D video
- Audio
  - Encode up to 4 audio streams
    - Up to 8 channels can be selected for mapping when SDI input carries more than 8 audio channels
    - Supports mapping between source channels and encoded audio channels
    - Contains 1 x 8-channel stream and 3 x 2-channel streams
  - Bitrate: 256/192/128/96/64/48/32/16 kbps
  - Output source embedded audio and line in through LINE OUT

## Live stream

- Natively supports streaming to:
  - Twitch
  - YouTube (HLS/RTMP), publishing to timeline or a new event and setting “made for kids”.
  - Facebook, enabling backup stream and publishing to timeline or a new event.
  - WOWZA over RTMP, adding token and publishing to timeline or a new event.
  - WOWZA over SRT, setting AES encryption (AES-128/192/256) and publishing to a channel or a new event.
- Supports streaming protocols:
  - RTSP
  - RTMP/RTMPS
  - SRT Caller/SRT Listener
  - NDI<sup>®</sup>|HX2/NDI<sup>®</sup> HX3
  - HLS
  - TS over UDP/TS over RTP
  - TVU ISSP
- Supports streaming to 6 destinations simultaneously, containing 1 session of RTSP/SRT Listener/HLS/ISSP (if included), or 2 NDI<sup>®</sup>|HX2 sessions (if included)
- Supports 1 NDI<sup>®</sup> HX3 sessions exclusively
- Supports specifying a video stream and an audio stream for each streaming session
- Supports live stream scheduler

## Record

- Supports setting and managing recording function and tasks
- Supports recording to local storage
  - Supports format and performance test
  - Automatically upload files to remote file storage platform including FTP server, Google Drive, and Dropbox
- Supports recording to external USB storage
  - Supported system format: FAT32, exFAT and NTFS
- Supports recording to network attached storage (NFS/CIFS)
  - Supported system format: NFS, CIFS
- Supports loop recording and normal recording
- Supports saving recording files in MP4, MOV or TS format
- Supports specifying a video stream and an audio stream for each recording task
- Supports customizing recording file name and prefix
- Supports splitting recording files by time
  - MP4, MOV: up to 4 hours
  - TS: no limit
- Supports exporting or downloading files through Web UI
- Supports recording scheduler

## Web UI

- Access Web UI via PC and smartphone
- View real-time device status
- Preview encoded video
- Set input sources
- Customize encoding parameters
- Manage streaming destinations, start/stop streaming, view streaming status
- Manage recording tasks and recorded files
- Set up to 8 overlays for each stream, including text, picture, and clock
- Update firmware

- Supports registering Magewell Control Hub for centralized management
- Supports Microsoft Edge/Firefox/Chrome/Safari/Opera web browsers

## API

- Provides APIs for 3rd party control system

## Network Connections

- Ethernet: 1x RJ45 port, 10/100/1000 Mbps Base-T
- IEEE 802.3af PoE
- Wi-Fi: 802.11 a/b/g/n/ac, Station and AP modes supported
- 4G/5G USB modem (not supplied)
- USB Net

## Input/Output Ports

- 2 x SD/HD/3G BNC ports
  - 1 x Input
  - 1 x Loop-through
- 1 x 3.5mm LINE IN
- 1 x 3.5mm LINE OUT
- 2 x USB Type-A

## Storage

- USB flash drive (not supplied): FAT32, NTFS, exFAT
- NAS (not supplied): NFS/CIFS

## Indicators

- LEDs indicating the status of power, input signal, streaming, Ethernet, Wi-Fi connection
- NDI tally lights (preview-green, program-red)

## Power Supply and Consumption

- DC 5V/3A
- Max power consumption: 8.72W

## Form Factor

- 106.6mm x 106.2mm x 25mm

## Accessories

- 1 x 5V Power Adapter
- 1 x USB Type A to Type B cable
- 1 x Wi-Fi Antenna
- 1 x T-bracke

## Screw Mounting Hole

- 2 x M3 threaded hole
- A standard 1/4"-20 socket provided by T-bracket

## Working Environment

- Operating temperature: 0 to 50 deg C
- Storage temperature: -20 to 60 deg C
- Relative humidity: 5% to 90% non-condensing